

INTRODUCTION 68000L-2-Oil dispenser




This product uses two islands, 2 refueling machines, and 4 refueling guns. CPU open protocol, you can contact the IC card management system. The built-in water tank has 2 positions, controlled by a valve, and can be switched between single/double use. The tanks are actually used. Capacity 68000L.



Equipped with dual warehouses, dual pumps, flow rate of 35 cubic meters per hour, liquid level system, high-level quotation, overflow alarm system, and fire extinguishing system



There are double manhole covers on the top, with a pressure of 24KPA and an all-weather automatic pressure relief device. The cables are set to withstand high temperatures and can reach 70 degrees.



Automatic control system, automatic accumulation, settings and other systems are controlled and linked here, data query, and touch buttons are used



Refueling equipment, retractable to 10 meters, automatic accumulation, dual pump and dual metering configuration, receipt printing function, 1-inch large flow configuration


40—68000L: ←

External maximum dimensions (Excluding the height of the guardrail)	Length	12192mm
	Width	2438mm
	Height	2100mm
Rated capacity	40m ³	
Unladen weight	16700kg	
Temperature	-40°C ~ 60°C	
Manhole diameter	580mm	
Emergency pressure relief value	21-35kPa	
Breathing valve	DN50 -295Pa~2000Pa	
Barrier explosion-proof materials	Type IV	
Paint	Epoxy zinc-rich primer + epoxy cloud iron intermediate paint + polyurethane topcoat	
Operating voltage	Three-phase five-wire 380V	
Maximum power consumption per unit when loaded	14Kw	

Built-in explosion-proof barrier material, the tank will not burn or explode when exposed to open flames. After testing, when a bullet passes through the tank, there is no fire or explosion inside, making the equipment absolutely safe.



Planning Approval



Configuration form

No.	Equipment Configuration List (Standard ● Option ○)	clarification	brand name
1	● Above-ground fire and explosion-proof double-walled fire-resistant storage tanks	USA-UL142 standard manufacturing 8mmQ235B	Desheng
2	● Electrostatic grounding lightning protection anti-static skid (support personalised)	Exterior three coats of paint, zinc-rich epoxy primer 80 microns, iron epoxy medium, polyurethane topcoat	Desheng
3	● Inlet and outlet oil lines stainless steel metal flexible tube (with anti-vibration universal coupling)	DN80 0.25Mpa	United States imports
4	● Explosion-proof material; Internal flame arrestor	AQ3002-2005 Provision IV profiles	Desheng
5	● Closed oil unloading system	Unloading port quick coupling DN80 Self-sealing ring valve;	Desheng
6	● Closed Oil Discharge System	DN40 oil outlet pipe, equipped with service protection device	Desheng
7	● Non-return device	Prevent the oil from flowing backward in the unloading pipeline after unloading to ensure the safety of the unloading process and at the same time meet the requirements of env-	Domestic Famous Brands
8	● Hanging automatic fire extinguishing dry powder device	Ultrafine dry powder fire extinguishing agent, filled with appropriate amount of driving gas nitrogen, technical performance in line with the GA78-94 standard, the device is equipped with temperature-sensitive glass nozzle nozzle part, the starting temperature of 68°C	Domestic Famous Brands

9	● Emergency Pressure Relief Device	When the internal pressure is too large and the breathing valve has not been able to play an effective role in pressure reduction, the emergency relief device will burst, play a rapid role in pressure reduction, the air volume of 7000m³/Min DN40 Emergency Shut-off Valve valve, normally open, such as the occurrence of a fire or emergency automatic disconnection of oil	Desheng
10	● Pressure Vacuum Breathing / Flame Arrestor Valves	Breathing valve working pressure 2kpa-3kpa, working pressure 1.5kpa-2kpa/ZFQ-1 C class	Desheng
11	● Mezzanine Leak Monitor	Tubular sight glass, tank leaks can be quickly detected	Domestic Famous Brands
12	● petrol dispenser	flameproof 220V/380V	Desheng
13	● Electronic Liquid Level Meter	Digital display high and low liquid level alarm reminder	Domestic Famous Brands
14	● Liquid Level Console	Visible tank liquid control height setting	Domestic Famous Brands
15	● Explosion-proof oil unloading systems	Vertical explosion-proof oil pump, flow rate 15MP/hour, head 20M, motor for explosion-proof type (dII), protection grade IP55/pipeline diameter DN80, unloading port quick coupling DN80 self-sealing ball valve	Domestic Famous Brands
16	● High-speed silent unloading pump	380V flameproof	Domestic Famous Brands
17	○ High and low level oil unloading automatic report system		Domestic Famous Brands
18	○ Automatic shut-off system for high liquid level unloading		Domestic Famous Brands
19	○ Heat insulation and fireproof board		Domestic Famous Brands
20	● Explosion-proof Intelligent Magnetic Level Meter	Magnetic Flip-Flop Level Meter	Domestic Famous Brands
21	● Anti-dry type intelligent magnetostrictive liquid level carbon rod	Precise measurement, level display	Domestic Famous Brands
22	● Explosion-proof distribution systems	Explosion-proof distribution box BXMD-61, 380V All circuit systems of the equipment are made explosion-proof and effectively grounded.	Domestic Famous Brands
23	● Explosion-proof lighting fixtures	Explosion-proof ceiling lamp, one-piece design, explosion-proof according to ExelT4	Domestic Famous Brands
24	● Oil and gas alarm devices	With concentration display and audible and visual alarms, installed at the refuelling site or in the valve room of the unloading pump, with sound intensity > 90 (db) or unloading pump valve room, sound intensity ≥ 90 (db), explosion-proof marking ExelBT4, protection class IP65.	Domestic Famous Brands
25	● Static Grounding Alarm System	Includes static earth alarm, aluminium electrostatic clamps for connection to unloading trucks. Aluminium electrostatic clips for connection to the tanker (3 metre wire at grounding end, 4 metre wire at clamping end), braided copper wire for grounding, 4 grounding electrodes (to ensure grounding resistance < 4Ω)	Domestic Famous Brands
26	○ Limited/Wireless IC Card Management System, Statement Printer, Ticket Printer	Options according to customer requirements	Domestic Famous Brands
27	○ Wireless Management System	Options according to customer requirements	Domestic Famous Brands
28	○ canopy	Options according to customer requirements	Desheng
29	● Primary/Secondary Oil and Gas Recovery Systems	National Standard Primary/Secondary Oil and Gas Recovery Treatment	Desheng

Integration of all electrical power switches; integrated liquid level and other data display; equipment abnormal monitoring and alarm functions (including but not limited to oil and gas concentration, unloading pumps, abnormal power failure, etc.) with the World T-level surge protector; the approval of the construction of a separate distribution room is not.

Working voltage: 380V/220V
Explosion-proof mark: Ex-delBT4Gb
Protection grade: IP65

switch box

Installed in the unloading operation site; aluminum electrostatic clips connected to the tanker; ensures that the electrostatic charge generated during the operation of the tanker is conducted into the ground; resistance <4Ω

Static Link Alarm

QZY type circular arc gear pump adopts the selected arc plus other curves compounded into a tooth pattern, with excellent working characteristics. It has small pressure fluctuation, low noise, high efficiency, long life, and is a new type of energy-saving pump.
Model: QZY42/20-2T-LG Pressure: 0.2MPa Speed: 1440r/min
Explosion-proof marking: Ex-delBT4Gb

Anti-corrosion and explosion-proof, high efficiency and environmental protection, high luminous efficacy, constant current output, stable performance, long service life, no extra maintenance, widely used in Sinopec, PetroChina, and other units.
Explosion-proof grade: delCT16
Protection grade: IP66

Explosion-proof lighting system for petrol bunkers

Ultra-fine dry powder fire extinguishers, filled with the appropriate Fort drive gas - nitrogen, technical performance in line with the GA7-8-04 standard, loaded with clouds of nozzle parts are equipped with a temperature-sensitive glass nozzle, the starting temperature of 68 ± °C

Suspended (68° C) automatic fire extinguishers

Installed in the petrol dispenser operation room outside, and explosion-proof intelligent safety monitoring (power distribution) installed place (single), such as class of emergency alarm signal, in order to facilitate the timely monitoring and handling of the site personnel abnormal quiet conditions.

Explosion-proof audible and visual alarms

When a leak occurs between the inner and outer tanks, it can be detected through the sight glass in time to provide a security alert. Complies with the national industry standard "AQ3002".

Double-walled leak-proof observation mirror

Equipped with audible and visual alarms, with concentration display and audible and visual alarms, for installation in refueling operations and unloading pump valves.

Control area oil and gas detection system

Fuses valves are mounted on the dispenser outlet line, they automatically shut off the outlet line when the temperature rises above 74 °C.

Emergency cut-off device

Explosion-proof vertical oil discharge pumps

Pneumatic seal	
Specification	
material	

Jiangsu Dashing Energy Equipment

CORE MONITORING FUNCTION

LIQUID LEVEL MONITORING

COMBUSTIBLE GAS CONCENTRATION
MONITORING LEAKAGE MONITORING
UNLOADING PUMP STATUS MONITORING
OIL UNLOADING FLOW METER



WORK ENVIRONMENT MONITORING

LIGHTING CONTROL

EMERGENCY STOP FUNCTION

