

Manhole Cover Product Specification

The manhole cover is installed on the top of the oil tanker; when the pressure inside the tank rises sharply, the emergency pressure relief device automatically releases the excess pressure. The cover is equipped with an intake/exhaust valve (P/V valve), suitable for light fuels such as gasoline, diesel, and kerosene. The manhole cover features a reserved blind hole for installing accessories such as optical sensors, vapor recovery valves, or oil measurement tubes.

Core Function: Emergency Pressure Relief Device Characteristics

- When the tanker is exposed to high-temperature conditions, the manhole cover can automatically vent the gas inside the tank to relieve pressure, ensuring transportation safety.
- Built-in P/V pressure regulating valve
When a pressure difference exists between the interior and exterior of the tank, the system automatically adjusts the air intake/exhaust process, balancing safety requirements with environmental protection standards.
- Secondary activation protection design
When activating the upper pressure plate, the internal pressure is released first, effectively ensuring the safety of the operator.

nominal diameter	20 inches
Emergency Start Pressure	21Kpa~35Kpa
Maximum discharge flow rate	7000m³/h
material quality	carbon steel
way to install	flange connection
operating temperature range	-40℃~+70℃

Tanker truck components: Manhole cover series

MT-GY801TB-560A

functional characteristics

- The large cover plate is fabricated from galvanized steel sheet through stamping process, offering impact resistance and oxidation resistance.
- Single or double P/V pressure valve configurations can be selected as needed.
- The base is manufactured using a roll welding process for sheet metal, facilitating easy welding to the tank body.
- Equipped with a dedicated key locking mechanism featuring a shock-absorbing rebound bayonet, ensuring stable locking and a leak-proof seal.



